



DS-2CE71H0T-PIRLO 5 MP PIR Turret Camera







- >> 5 MP CMOS
- >> 2560 × 1944 resolution
- >> 2.8 mm, 3.6 mm fixed focal lens
- >> PIR detection, strobe light alarm, alarm out
- >> Smart IR, up to 20 m IR distance
- >> IP67
- >> HIKVISION-C



HIKVISION
Authorised Reseller



 Camera	
Image Sensor	5 MP CMOS
Signal System	PAL/NTSC
Frame Rate	PAL: 5MP@20fps, 4MP@25fps, 4MP@12.5fps, 1080p@25fps NTSC: 5MP@20fps, 4MP@30fps, 4MP@15fps, 1080p@30fps
Resolution	2560 (H) × 1944 (V)
Min. Illumination	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/12.5 s to 1/50, 000 s NTSC: 1/15 s to 1/50, 000 s
Lens	2.8 mm, 3.6 mm fixed lens
Horizontal Field of View	85.5° (2.8 mm), 80.1° (3.6 mm)
Lens Mount	M12
Strobe Light Alarm	Yes
Day & Night	ICR
WDR	Digital WDR
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 75°, Rotate: 0° to 360°
 Menu	
White Light	Alarm/Off
Image Mode	STD/HIGH-SAT
AGC	Yes
Day/Night Mode	Auto/Color/BW (Black and White)
White Balance	Auto/Manual
AE (Auto Exposure) Mode	DWDR/BLC/HLC/Global
Noise Reduction	2D DNR
Language	English
Functions	Brightness, Sharpness, Mirror, Smart IR
 Interface	
Video Output	1 HD analog output
Alarm	1 alarm out
 General	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensing)
Power Supply	12 VDC ± 25%
Power Consumption	Max. 3.5 W
Ingress Protection	IP67
Material	Enclosure: Plastic Main body: Metal
IR Range	Up to 20 m
PIR Angle and Range	Angle: 110°, Range: 11 m
White Light Range	Up to 20 m
Communication	HIKVISION-C
Dimensions	Φ 109.8 mm × 89.75 mm (Φ 4.32" × 3.53")
Weight	Approx. 327 g (0.72 lb.)